

Packaging Dynamics, Ltd.

35B Carlough Road ◆ Bohemia, New York 11716 Telephone: (631) 563-4499 ◆ Fax: (631) 563-4893

EMAIL: DLEHM19148@AOL.COM

- CONVEYORS -



WWW.PACKAGINGDYNAMICS.COM

ENGINEERED FOR CONVENIENCE AND DURABILITY

Packaging Dynamics, Ltd conveyors come in a variety of custom configurations and lengths. Supplied with a Baldor variable speed drive, each conveyor includes table top chain or belt and standard 110/220 VAC supply voltage. Each conveyor contains adjustable stainless steel guide rails, stainless steel end cap guards, and adjustable height stands with foot pad levelers.

Conveyors can be equipped with *Transfer Plates, Product Diverters, Bi-Directional and Serpentine Accumulators.* Stainless steel construction provides for ease of cleaning with a minimum down-time. Optional configurations include 90° and 180° turn sections. Systems can be made with Nema 4 or explosion-proof electrics.

SPECIFICATIONS

DESCRIPTION

Container Size Range	1 oz to 5 gal
Drive motor	AC or DC
Controls	Inverter or DC-SCR drive
Construction Material	Stainless steel with guide rails and end plates
Overall Dimensions	As required
Electrical Requirements	110/220 VAC
Weight	Model & size dependant

OPTIONS

- ♦ Nema 4 electrics
- ♦ Explosion-proof electrics
- ♦ Product diverters
- ♦ Bi-directional & serpentine accumulators
- ♦ Sanitary design
- ♦ 45 & 90 Degree Turn Sections
- ♦ Elevation Type

- Stainless steel chain
- ♦ Chemical resistant chain
- Stainless steel transfer plates
- ♦ Zero gap transfer design
- ♦ AC Inverter Drive Speed Control
- Custom designs & Layouts